

Ins-30052 OEM hands free keyfob

Suitability

Compatible with hands free readers ✓

Compatible with non hands free readers ✓

The keyfob has been designed with features to extend battery life. This includes the prevention of repeated access requests to the same door whilst the keyfob remains within range. However, keeping the keyfob in the field of a reader can still reduce battery life to 12 months or less.

Battery replacement

Remove the small retaining screw. Insert a flat head screw driver into the groove in the corner below the screw position (see diagram) and gently twist to prise the case open.

Replace the battery, clip the cover closed and secure with the retaining screw.



SAFETY WARNING

RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE.

DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS

Specifications

		Min	Max
Dimensions			
Width	28 mm		
Height	12 mm		
Length	49 mm		
System Specification			
Carrier frequency - EM 4100	125 kHz		
	2.4 GHz		
Environment			
Operating temperature - Battery limits		0 °C	55 °C
Typical Battery Life		3 years	
Battery Type	CR2032		
Read range with hands free token			
P38			850 mm
P50			1100mm
P75			1500 mm
P200			2500 mm
P200E metal mount			2000 mm
Long range reader			5000 mm

Ins-30052 OEM hands free keyfob

Suitability

Compatible with hands free readers ✓

Compatible with non hands free readers ✓

The keyfob has been designed with features to extend battery life. This includes the prevention of repeated access requests to the same door whilst the keyfob remains within range. However, keeping the keyfob in the field of a reader can still reduce battery life to 12 months or less.

Battery replacement

Remove the small retaining screw. Insert a flat head screw driver into the groove in the corner below the screw position (see diagram) and gently twist to prise the case open.

Replace the battery, clip the cover closed and secure with the retaining screw.



SAFETY WARNING

RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE.

DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS

Specifications

		Min	Max
Dimensions			
Width	28 mm		
Height	12 mm		
Length	49 mm		
System Specification			
Carrier frequency - EM 4100	125 kHz		
	2.4 GHz		
Environment			
Operating temperature - Battery limits		0 °C	55 °C
Typical Battery Life		3 years	
Battery Type	CR2032		
Read range with hands free token			
P38			850 mm
P50			1100mm
P75			1500 mm
P200			2500 mm
P200E metal mount			2000 mm
Long range reader			5000 mm